

Pneumatic Tacker

371/16-401

This model of the BeA 400 series is among the lightest tackers in this tool series with bottom loading magazine. High penetration power, low air consumption, integrated silencer and its modern design make this tacker an industry standard. The standard magazine takes approximately 200 fine wire staples type 71 from 5/32" to 5/8" in length.

Popular Applications

Furniture upholstery, seats, radio and television, cabinets, speaker grills, wicker work.



Technical Data

Model:	371/16-401 Standard	371/16-401 L Long magazine
Part number:	12000032	12000034
Loading type:	bottom loading	bottom loading
Staple type:	71	71
Magazine capacity:	189	392
Staple sticks:	1 x 182	2 x 182
Air pressure range:	75-90 P.S.I.	75-90 P.S.I.
Maximum air pressure:	90 P.S.I.	90 P.S.I.
Air consumption:	.01 cu. ft./cycle @ 90 P.S.I.	.01 cu. ft./cycle @ 90 P.S.I.
Recommended hose I.D.:	ø 3/8"	ø 3/8"
Weight:	1.82 lbs.	2.42 lbs.

Items supplied with tool: Operating instructions, spare parts list, service instructions.

Subject to technical modification.

Accessories:

Part number	Description
14403330	Remote firing valve
14403535	Stationary mounting fixture

All BeA pneumatic tools can be jig-mounted. We supply the necessary accessories.



This tool conforms to the EC Directive for Machinery (89/392 EWG)


Pneumatic Tacker

371/16-401



BeA Fasteners U.S.A.
2100-120 Fairfax Road
Greensboro, NC 27407
Phone: (336) 510-4232
Fax: (336) 510-4233

Staple type 71



Description	L = Length inches
71/4NK	5/32"
71/5 NK	3/16"
Other lengths and finishes are also available on request.	

Fastener nomenclature:

NK = Galvanized steel
NKS = Galvanized steel, high carbon
BK = Brite steel
BKS = Brite steel, high carbon

HZ = Resin coated
NR = Stainless steel
DP = Divergent point