

Pneumatic Tacker

97/16-407

A lightweight well-balanced tacker, thanks to its ergonomic design. Excellent driving power. A multi-purpose tool for industry and the do it yourself. Large magazine capacity, with a wide range of staple lengths from 1/4" to 5/8", and its low air consumption make this BeA tool a cost reducer.



Popular Applications

Upholstered furniture, cabinets, toy manufacturing, wicker work, light wooden products, picture frames

Technical Data

Model:	97/16-407
	Standard
Part number:	12000048
Loading type:	bottom loading
Fastener type:	97
Magazine capacity:	156
Standard load, strips x fasteners/strip:	1 x 100
Working pressure:	75-90 P.S.I.
Maximum air pressure:	90 P.S.I.
Air consumption:	.01 cu. ft./cycle @ 90 P.S.I.
Recommended hose I.D.:	ø 3/8"
Weight:	1.98 lbs.

Items supplied with tool: Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

Accessories

Part number	Description
14400827	Adjustable roller edge guide
14400870	Heeling stop
14403330	Remote firing valve assembly
14403535	Stationary mounting fixture

All BeA pneumatic tools can be jig mounted
We supply the necessary accessories



This tool conforms to the EC Directive
for Machinery (89/392 EWG)


Pneumatic Tacker

97/16-407



BeA Fasteners U.S.A.
2100-120 Fairfax Road
Greensboro, NC 27407
Phone: (336) 510-4232
Fax: (336) 510-4233

Fastener type 97



Part number	Description	L = Length in.
10000451	97/08 HZ	1/4"
10000457	97/08 HZ	5/16"
10001746	97/10 HZ	3/8"
10000469	97/12 HZ	1/2"
10000478	97/14 HZ	9/16"
10000485	97/16 HZ	5/8"

Other lengths and finishes are also available on request.

Fastener nomenclature:

NK = Galvanized steel
NKS = Galvanized steel, high carbon
BK = Brite steel
BKS = Brite steel, high carbon

HZ = Resin coated
NR = Stainless steel
DP = Divergent point