

Pneumatic Tacker Type 98/25-551

The BeA 98/25-551 is a light and powerful tool, that drives type 98 staples in length from 10 to 25 mm. The bottom loading magazine allows for quick and easy reloading, the long slender nose allows fastening even in hard to reach areas and provides better visibility for more precise fastener placement.

The cycle speed of the automatic version can be infinitely varied between 0 – 900 staples per minute. Without adjustment an exact stapling can be achieved even at highest operation speed, thus optimizing the staple consumption and reducing time requirement.



Popular applications:

Cabinetry, trim & moldings, shutter louvers, lattice panels, picture frames.

| | |
|---------|--------|
| Length: | 203 mm |
| Width: | 47 mm |
| Height: | 178 mm |

Technical data

| Type description: | 98/25-551 Standard / Single | 92/25-551 A Automatic |
|---|--------------------------------|--------------------------|
| Article code: | 12000157 / 12000291 | 12000356 |
| Magazine type : | Bottom loader | Bottom loader |
| Safety: | - / Single actuation | - |
| Fastener type: | Type 98 | Type 92 |
| Magazine capacity: | 168 | 168 |
| Fasteners per strip: | 1 x 100 | 1 x 100 |
| Operating pressure: | 5 – 6 bar | 5 – 6 bar |
| Max. operating pressure: | 6 bar | 6 bar |
| Air consumption/operation: | 0,45 litre / 6 bar | 0,45 litre / 6 bar |
| Trigger frequency: | - | 0 – 900 per min. |
| Inner hose diameter: | Ø 9 mm LW recommended | Ø 9 mm LW recommended |
| Emission sound pressure level at the workstation: | L pA, 1s, d= 80 dB | L pA, 1s, d= 80 dB |
| Single-shot emission sound pressure level: | L WA, 1 s,d= 88 dB | L WA, 1 s,d= 88 dB |
| Weight: | 1,23 kg | 1,23 kg |

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

| Articel code | Description |
|--------------|--|
| 14400827 | Adjustable roller edge guide (assembly in factory) |
| 14405489 | Adjustable roller edge guide (assembly in factory) |
| 14405569 | Remote Valve |
| 14405571 | Mounting flange |

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Pneumatic Tacker Type 98/25-551

Staples type 98



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



| Description | L = Length mm |
|-------------|------------------|
| 98/10 NK HZ | 10 |
| 98/12 NK HZ | 12 |
| 98/14 NK HZ | 14 |
| 98/16 NK HZ | 16 |
| 98/19 NK HZ | 19 |
| 98/25 NK HZ | 25 |

Other lengths and finishes are also available on request.

Explanations:

| | | | |
|------------------------------------|--------------------------------|--|----------------------|
| NK = galvanized steel | BK = bright steel | LM = aluminium | HZ = resin coated |
| NKS = galvanized steel, extra hard | BKS = bright steel, extra hard | NR = stainless steel, material. 1.4401 | DP = divergent point |
| NKH = galvanized steel, hard | MS = brass | RF = rust resistant, material 1.4301 | SA = step cut |