

Pneumatic Tacker

71/16-436 LN

A variation of the successful upholstery tacker 71/16-421. The 2" long nose allows for ease of entry into hard-to-reach areas. Low weight, high driving power combined with an integrated silencer and low air consumption are the outstanding features of this tacker.

Popular Applications

Upholstery, case goods, boat seating, headers, automotive and RV industry.



Technical Data

Model:	71/16-436 LN Long nose
Part number:	12000074
Loading type:	Bottom loading
Staple type:	71
Magazine capacity:	190
Standard load, strips x staples/strip:	1 x 182
Air pressure range:	75-90 P.S.I.
Maximum air pressure:	90 P.S.I.
Air consumption:	.017 cu. ft./cycle @ 90 P.S.I.
Recommended hose I.D.:	ø 3/8"
Weight:	2.31 lbs.
Items supplied with tool:	Operating instructions, spare parts list, service instructions.

Subject to technical modification.

Accessories:

Part number	Description
14403330	Remote firing valve assembly
14406166	Back nose assembly set 1/4" staples and shorter only

All BeA pneumatic tools can be jig-mounted.
We supply the necessary accessories.



This tool conforms to the EC Directive
for Machinery (89/392 EWG)


Pneumatic Tacker

71/16-436 LN



BeA Fasteners U.S.A.
2100-120 Fairfax Road
Greensboro, NC 27407
Phone: (336) 510-4232
Fax: (336) 510-4233

Staple type 71



Description	L = Length inches
71/06 NK	1/4"
71/08 NK	5/16"
71/10 NK	3/8"
71/12 NK	1/2"
71/14 NK	9/16"

Other lengths and finishes are also available on request.

Fastener nomenclature:

NK = Galvanized steel
NKS = Galvanized steel, high carbon
BK = Brite steel
BKS = Brite steel, high carbon

HZ = Resin coated
NR = Stainless steel
DP = Divergent point