

Pneumatic Tacker Type 95/14-455 AL

The ideal tacker for industrial purpose. Gives best performance wherever quick and durable fastening is required. The cycle speed can be infinitely varied between 0 – 1600 staples per minute. Without adjustment an exact stapling can be achieved even at highest operation speed, thus optimizing the staple consumption and reducing time requirement. The long magazine reduces the reloading frequency.



Popular applications:

Insulation, fastening of foils etc.

Automatic Long

Length: 347 mm
Width: 40 mm
Height: 149 mm

Technical data

Type description:	95/14-455 AL Automatic
Article code:	12000081
Magazine type :	Bottom loader
Safety:	-
Fastener type:	Type 95
Magazine capacity:	208
Fasteners per strip:	2 x 100
Operating pressure:	5 – 6 bar
Max. operating pressure:	6 bar
Trigger frequency:	0 – 1600 per min.
Air consumption/operation:	0.3 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 77 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB
Weight:	1,34 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, allen keys SW 8, SW 13, silencer.

Subject to technical modifications.

Accessories:

Articel code	Description

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Product leaflet 455 AL

Pneumatic Tacker Type 95/14-455 AL

Staples type 95



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

A division of
Joh. Friedrich Behrens AG

Description	L = Length mm
95/08 NK	8
95/10 NK	8
95/12 NK	10
95/14 NK	14

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut