

Pneumatic Tacker Type 71/16-421

The light but powerful tacker of the 420 series takes staples type 71 in leg lengths from 6 mm to 16 mm. The low air consumption, long service life and ease of maintenance of this tacker make it a real cost saver. The bottom loading magazine allows easy and quick loading. Further features are the ergonomic design and the integrated silencer. This is a versatile tool for industry and the craftsman.



Popular applications:

Upholstered furniture, chairs, TV and stereo cabinets, loudspeakers, wicker and rattan furniture, perambulators, automobile industry

Length: 221 mm
Width: 43 mm
Height: 144 mm

Technical data

Type description:	71/16-421 Standard / Contact	71/16-421 Profile
Article code:	12000063 / 12000065	12000324
Magazine type :	Bottom loader / Bottom loader	Bottom loader
Safety:	- / Contact actuation	-
Fastener type:	Type 71 / Type 71	Type 71
Magazine capacity:	190 / 190	190
Fasteners per strip:	1 x 182 / 1 x 182	1 x 182
Operating pressure:	5 – 6 bar / 5 – 6 bar	5 – 6 bar
Max. operating pressure:	6 bar / 6 bar	6 bar
Air consumption/operation:	0,3 litre / 6 bar / 0,3 litre / 6 bar	0,3 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB	L WA, 1 s,d= 87 dB
Weight:	0.94 kg / 1,9 kg	0.97 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code	Description
14400827	Adjustable roller edge guide (assembly in factory)
14400838	Adjustable roller edge guide (assembly in factory)
14405948	Back nose assembly set 6mm
14405424	Cap, Alu
14403330	Remote valve, compl.
14403330	Remote valve, compl.

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Pneumatic Tacker Type 71/16-421

Staples type 71



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
71/06 NK	6
71/08 NK	8
71/10 NK	10
71/12 NK	12
71/14 NK	14
71/16 NK	16

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut