



For wire collated
BDC nails



BeA Pneumatic Nailer 830 DC

For nails: BDC 2.5 - 3.3 mm in the lengths of 50 - 83 mm

- Extremely powerful and sturdy
- Adjustable exhaust
- Integrated sound absorption
- Ergonomic handgrip, operator friendly
- Dust and dirt protection
- Reinforced nose piece
- Thread for mounting
- Tool body protection

Applications

Siding / cladding, sheathing, sub flooring, pallets,
boxes and cases, house construction



BeA 830 DC

Technical Data




Article code	12100457
EAN code	4045759047469
Magazine type	Top loader
Weight	3.8 kg
Dimensions in mm	L 307, H 361, B 132
Safety system	Contact actuation
Fastener type	Type BDC
Magazine capacity	max. 225 – 300 nails
Operating pressure	5 – 8 bar
Max operating pressure	8 bar
Air consumption/operation	3.68 litre / 6 bar
Inner hose diameter	9 mm recommended
Emission sound pressure level at the workstation	$L_{pA, 1s, d} = 94.8 \text{ dB}$
Single shot emission sound pressure level	$L_{WA, 1s, d} = 101.0 \text{ dB}$
Vibration level as per ISO 8662-11 is	3.12 m/s^2 .
Accessories	Operating instructions, spare parts list, service instructions, allen wrench, oil, safety glasses

Coil nails BDC

BDC nails = wire welded coil nails

Width	2.5 – 3.3 mm
Length	50 – 83 mm
Material	BK = steel, bright NK = steel, electro galvanized RF = stainless steel, comparable to material 1.4301 NR = stainless steel, comparable to material 1.4401 FV = steel, hot dipped galvanized
Surface properties	Smooth Ring shank Screw shank
Nail heads	Flat head Dome head Pozi head Torx head



BDC: 50 – 83 mm

Further types on request, nails conforming to DIN1052 and to EN 14592 (Eurocode 5)

Joh. Friedrich Behrens AG
Industrielle Befestigungssysteme
Bogenstraße 43 – 45
22926 Ahrensburg
Germany

Further Information:
Phone: +49 (0) 41 02 78 - 283
Fax +49 (0) 41 02 78 - 275
Email: info@bea-group.com
www.Bea-Group.com

BeA is a member of the following trade associations:

